




**Product Family**  
**North Butyl™ - B254GI**

Unsupported Butyl gloves. Butyl has the highest permeation resistance to gas and water vapor, highly resistant to ketones (MEK, MIBL, acetone) and esters (tricresyl phosphate, amyl acetate, ethyl acetate). Available in smooth finish or Grip-Saf™ palm for enhanced grip. Available in a variety of sizes, lengths and mil thicknesses.



**Product Numbers & Ordering Information**

Product Numbers	Details
 B254GI	<b>North® Butyl Gloves</b> Butyl, unsupported, sanitized interior, 14 in / 25 mil, smooth finish, rolled bead cuff, are manufactured to the requirements of MIL - DTL - 43976D additional requirements of testing and packaging are special order

**Packaging Information**

1 pair per pack, 50 pair per case

**Overview**

**Key Features**

Unsupported Butyl gloves. Butyl has the highest permeation resistance to gas and water vapor, highly resistant to ketones (MEK, MIBL, acetone) and esters (tricresyl phosphate, amyl acetate, ethyl acetate). Available in smooth finish or Grip-Saf™ palm for enhanced grip. Available in a variety of sizes, lengths and mil thicknesses.

**Recommended Industries/Use**

- Chemical
- Manufacturing
- Municipal Services
- Utilities

**Hazards**

- Chemical

**Regulations**

- ANSI/ISEA 105 - ASTM D3389-05 Abrasion Test
- ANSI/ISEA 105 - ASTM F1790-97 Cut Test
- EN374 - Permiation and breakthrough time
- EN388 - Mechanical risks from abrasion, cut, tear and puncture
- EN420 - General Requirements - This standard defines the general requirements for protective gloves in terms of construction, fitness of purpose and safety.
- OSHA Standard -29 CFR 1915.157 - The employer shall ensure that each affected employee uses appropriate hand protection and other protective clothing where there is exposure to hazards such as skin absorption of harmful substances, severe cuts or lacerations, severe abrasions, punctures, chemical burns, thermal burns, harmful temperature extremes, and sharp objects.

**Warranty Information**

LIMITED WARRANTY. Except for any warranty for a particular product or part specifically stated in our product literature, we warrant all goods sold under this agreement against defects in materials and workmanship for one year from shipment. In the event of such defects, we will, at our sole option and as your exclusive remedy, repair or replace the defective product without charge, or refund the price you have paid. In order for this warranty to be effective, you must notify us within 15 days of discovery of the defect. you must return the defective product to us within the warranty period, properly packaged and with insurance and transportation costs prepaid. We will reship the product to you at our expense in the United States. Products will conform to Honeywell published specifications if properly used and maintained and will be free from defects in materials and/or workmanship. no changes to Honeywell published specifications will be valid without Honeywell written consent. This warranty does not cover defects which we determine are because of accident, alteration, modification, negligence, misuse, abuse failure to perform adequate maintenance, or normal wear and tear.

**Specifications****Ambidextrous or Hand Specific**

- Hand specific

**Coating**

- NA

**Coating Color**

- NA

**Coating Pattern**

- NA

**Construction**

- Dipped

**Cuff**

- Rolled bead

**Gauge / mil**

- 25 mil

**Glove Type**

- Chemical resistant

**Length**

- 14 inch

**Liner**

- None

**Material**

- Butyl

**Material Color**

- Black

**Overedge**

- NA

**Supported or Unsupported**

- Unsupported

**Surface Finish**

- Smooth finish

**Additional Information**

Manufactured on govt. spec. APM hand forms and are built with the intention of meeting the requirements of MIL-DTL-43976D but are not fully tested, inspected, marked or packaged in accordance with this specification. Further testing and inspection at a government laboratory is available upon request at an additional charge.

## Technical Support

Technical Support is available Monday through Friday, 8:00 AM to 7:00 PM EST. 1.800.873.5242  
hsptechsupport@honeywell.com

© Honeywell International Inc.